

SCREENKING®

S30

S50

S70

S120

TROMMEL BUCKETS





Quarry Application



Quarry Application




Disposal Application



Good Balance, easy to operate



Filtering sand away from macadam



Wide range of screen sizes



CAD designed excellent geometry for optimum bucket linkage curling radius

Features

- Compact design and functional structural frame makes this attachment lightweight and easy to operate.
- A built-in control valve regulates flow and pressure, eliminating the need for costly plumbing on the carrier excavator.
- A double-acting single pump flow kit used to run a thumb, crusher or shear is all that is needed to achieve two-way rotation.
- The in-body control valves allow the drum rotation speed to be fine-tuned for smooth operation in a variety of applications.
- The rotation drum consists of four bolt-on concave screens that are easily replaced, eliminating costly downtime.
- An assortment of screen sizes from 3/8" (9 mm) to 4" (100 mm) are available, making it suitable for a variety of screening processes.
- Large capacity makes it the most productive trommel bucket in its weight class.

		S30	S50	S70	S120
Approx. operating weight	lbs	1325	2650	3970	6174
Overall length	inches	65.6	93.3	100.8	116.7
Overall height	inches	51.2	63.8	68.5	78.4
Overall width	inches	42.5	55.9	63.4	66.1
Screen diameter	inches	32.7	43.3	47.2	55.1
Screen length	inches	37.4	49.2	55.1	63
Drum capacity	yd ³	0.7	1.6	2.1	3.2
Operating pressure	psi	3000	3000	3000	3000
Carrier weight range	US tons	6-9	10-18	20-25	33-38
Recommended oil flow	gpm	17	30	54	75
Oil flow range	gpm	16-35	26-42	44-64	57-80

Specifications are subject to change without notice.



R.R. Equipment Company

5550 Charlotte Hwy
Lancaster, SC 29720

803.416.5200

803.416.5202

www.rrequipment.com